



# AFW

## SERIES

THE HEAVY DUTY BENCH/FLOOR SCALE





# AFW

## COMMON FEATURES

- OIML-R76 and EC Class III Type Approved
- Flexible Platform Collocation
- Rugged Designed and Constructed Mold Injected Aluminum Alloy Platform
- Overload Protection Devices Against Excessive Load or Shock Applied
- Press Formed Corrosion Resistant Stainless Steel Cover
- Designed to Meet Industrial Application Requirements
- User Programmable Capacity and Division
- Equipped with Power On Zero Tracking, Re-zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, Auto Tare, Accumulation Memory and Dual Interval Selection\*\*
- Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- Long Battery Operating Time: AFW: 200 Hours Plus
- Complete with Low Battery and Charging Status Indicator
- 5 1/2 x 25mm Oversize Wide Angle LCD Digits
- Adjustable Feet, Rechargeable Battery, Power Adaptor, Bubble Level and Indicator Dust Cover Included

\*\*Depends on R60 approval grade of the load cell used

## DISPLAY RESOLUTION: - OIML APPLICATIONS

- Standard = 3000
- Maximum = 30000 Under Extended Display Mode

## DISPLAY RESOLUTION: - NON-OIML APPLICATIONS

- User Programmable
- Recommended = 6000 to 7500
- Maximum = 30000

## OPTION AVAILABLE

- EL Backlight
- RS232C Interface Output

## SPECIFICATIONS



Model No.	Capacity	Recommended Display Resolution		Platform	Individual Package
		OIML Application	Non-OIML Application		
AFW-B30	30kg	0.01kg	0.005kg	330 x 450mm Mold Injected Aluminum Alloy with Stainless Steel Cover	805(L) x 490(W) x 220(H)mm Net/Gross Weight: 11.2/13.7kg
AFW-B60	60kg	0.02kg	0.01kg		
AFW-B150	150kg	0.05kg	0.02kg		
AFW-F60	60kg	0.02kg	0.01kg	425 x 525mm Mold Injected Aluminum Alloy with Stainless Steel Cover	880(L) x 640(W) x 210(H)mm Net/Gross Weight: 17/21kg
AFW-F150	150kg	0.05kg	0.02kg		
AFW-F300	300kg	0.1kg	0.05kg		
Tare Range	OIML = 1/3 Max. - e Non-OIML = Full Range				
Operating Environment	0° - 40°C (32° - 104°F), Non-condensed R.H. ≤ 85%				
Power Source	By Built-in Rechargeable Battery or AC/DC Power Adaptor				

Specifications subject to change without notice



## UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsin Taiwan R.O.C.  
Tel: +886-2-29180121 (12 Lines) Fax: +886-2-29181508 - 29183652 - 29112176-7  
http://www.uwe-scale.com.tw e-mail:uwe@ms8.hinet.net

Oct '2002 Designed by DARY  
Printed in Taiwan